UPV Check-off Sheet	UNINSPECTED PASSENGER VI	ESSEL				
Vessel Name:	POC:		Phone:			
EXAMINER:	DATE:	_ Vesse	el Representative:			_
** indicates a su	uggestion – not a requirement for the	decal				
1 NUMBERING				SAT	UN-SAT	N/A
Documented vessels: vessel na	ame and hailing port on stern, minimum 4"	lettering	46CFR 67.123			
Documented vessels: vessel na	ame on port & starboard bow, minimum 4"	lettering	46CFR 67.123			
		33CFR 173.27				
minimum 3" block-type Arabic num			ABYC T-10.3			
Not documented: State Number	rs & validation sticker displayed		33CFR 173.35			
Examination notes: markings clearly	ly visible, contrasting color to background					
2 REGISTRATION/	DOCUMENTATION Doc #:					
	(about 25 ft.), documented for coastwise trade		46CFR 67.15			
Documented vessels: original documentation certificate on hoard. properly endorsed (e.g. coastwise trade, recreation) and valid		46CFR 67.7 & 163				
Not documented: original state nur	mbering certificate on board		33CFR 173.21			
3 PERSONNEL - US	GCG LICENSE License Doc #:		Expir date:			
Operator has proper USCG license	e (Operator UPV or Master license)		46CFR 15.605 & .905			
Origional License in operator's pos	ssession on board the vessel		46CFR 26.20-1(a)			
Operator is licensed for waters navigated		46cfr 15.401				
** Aware of Sufficient number of operators for two watches (if voyage over 12 hours)		46USC 8104(b)				
	plicable for vessel operation and tonnage. Check for record DC - License should be signed ~ Record DC - ATION NUMBER HIN:		ns. Original license on board Mate	ch identifica	tion on license	against
If documented vessel, use the	he DOC # as HIN	33CFR 181.23 / ABYC T-10				
5 NAVIGATION LIG	GHTS					
Proper navigation lights			34 / ABYC A-16.5.2			
All around anchor light			34 / ABYC A-16.6.5			
6 ANCHOR & ANC	HOR LINE					
** Suitable for vessel with sufficient anchor line for area of operations		ABYC H-40.4				
7 SOUND PRODUC	·					
Whistle or Horn	histle or Horn 33 CFR 8		6.23 / ABYC A-23.5			
Examination notes: Athletic whist	le not acceptable for vessels over 12 meters (39	9.4 ft)				
8 RING LIFE BUOY	Number of:					
	for vessels > 26 ft. at least 20 inch size	ze.	46 CFR 25.25-5(d)			
Immediately available	-		46 CFR 25.25-9			
Buoyant 3/8" grab line		46 CFR 160.050				
CG Approval			46 CFR 160.050			
Type 1 reflective tape is NOT REQUIRED on the ring life buoy.		46 CFR 25.25-15				

Examination notes: Can he orange or white. Must be orange if vessel goes into Canada. Lifeline not required. Grab line should he equally spaced in 4 quadrants. Test beckets and grab line for durability. Vessel < 26 ft are required to carry aboard at least one Type IV throwable device, e.g. buoyant cushion. For vessels > 65 ft 3 are required

Vessel Name: DATE:					
9 BELL	BELL			UN-SAT	N/A
Required in addition to whistle or horn on vessels >65 ft.	33CFR 8	33CFR 86.23 ABYC A-23.5 c			
Examination notes: < 65 ft. Can use equipment having the same sound cha	racteristics in lie	ı of bell (e.g. electronic device)	•	
10 PERSONAL FLOTATION DEVICES Number of Ad	lul+•	Child:			
				Ī	1
Type 1 CG approved PFD of suitable size for each person		46CFR 25.25-5(c)(f) 46CFR 25.25-15			
Type I reflective material on each PFD PFD device light (make sure batteries are surrent) Fyn Date:		46CFR 25.25-15 46CFR 25.25-1			
PFD device light (make sure batteries are current) Exp.Date:					
Readily accessible ~ (only Type I PFDs in the locker)		46CFR 25.25-9			
In serviceable condition # Adult # Child		46CFR 25.25-11			
USCG approval numbers visible		46CFR 25.25-7			
Life Floats: (not required) # of: Capacity:					
11 FIRE EXTINGUISHERS Number of B1: B2	:: F	ixed system:	_ insp d	late:	
USCC amazavad mantahla autia suiahana		46CFR 25.30-5(5)			
USCG approved portable extinguishers		ABYC A-4.6.1			
USCG approved <i>or</i> CERTIFIED for marine use		ABYC A-4.7.1			
Manufacturer name plate attached giving specifications		46CFR 26.30-10(d)			
Minimum number of portable extinguishers		46CFR 25.30-			
With no fixed system in engine spaces:		20(a)(1)&)b)(1)			
> 26 ft, less than 40 ft at least 2 B-1 portable extinguishers		TABLES ABYC			
> 40 ft, less than 65 ft at least 3 B-1 portable extinguishers		A-4.6.3			
Pressure gauge or indicating device		46CFR 25.30-10(h)			
Proper bracket for B-II extinguishers		46CFR162.028-3(g)			
Examination notes: If mfg date before 1/1/65 and not fitted with gauge, mus	t he weighed eve		tact and n	not damaged o	or leaking
(46CFR 25.30-10(g)) Record Number of each Type: Adult:		ld:	aot ana n	ot damagou c	, rouning
12 VISUAL DISTRESS SIGNALS					
				1	I
Date Current Record Expir. date:		33CFR 175.120 33CFR 175.125			
<u> </u>		33CFR 175.128		+	
CG Approval	h				
Examination notes: 3 day and 3 night or 3 day/night combination / ** s	hould be in a we	atherproof case			
13 CG CAPACITY PLATE					
Visible plate for monohull power vessels < 20 ft.	33CFR 8	84 / ABYC A-16.5.2			
	•	•			
Examination notes: This plate must be marked with the number of persons			-	e maximum w	eight
capacity in pounds, and the maximum horsepower for that boat or the word	s "This Boat Not	Rated for Propulsion by motor	··· .		
14 CERTIFICATE OF COMPLIANCE LABEL					
Required for monohull power vesssels < 20 ft. ABYC H-40.4					
Examination notes: This label is affixed by the boat's manaufacturer and she Guard Safety Standards in Effect on the Date of Certification".	ould contain the	following statement: "This Boa	nt Complie	es with U.S. C	oast
15 VENTILATION - Gasoline Engine					
		36.23 / ABYC A-23.5			
		36.23 / ABYC A-23.5			
Exhaust blower must work if vessel was built after July 1980 Lines)C 32 / ADVC A 32 F			
must be in lower 1/3 of compartment above bilge water	33 CFK 8	36.23 / ABYC A-23.5			<u> </u>
Examination notes: Each fuel tank and engine compartment vented with 2 v	onte fittad with c	owle: 1 exhaust 1 Intake Ch	ock for ho	Nos loaks Ch	nock

Examination notes: Each fuel tank and engine compartment vented with 2 vents fitted with cowls: 1 exhaust, 1 Intake. Check for holes, leaks. Check direction of exhaust discharge/ See 33CFR 183.520 & 175.201 for venting fuel tanks. Ensure flame screens on vents are properly fitted and not painted over or gummed over. Vent screens required.

Vessel Name: DATE	.:				
16 BACKFIRE FLAME ARRESTER - Gasoline	Engine		SAT	UN-SAT	N/A
For Gasoline engines; properly installed and clean			<u> </u>	† <u> </u>	
Examination notes: CG no longer approves backfire flame arrestors good condition & serviceable	, however, CG approval	numbers 162.015 or 162.042	can be co	ntinued in use	if in
17 FUEL SYSTEM					
Fuel pump & Filters not leaking		3.524 ABYC H-24.14.4			
Fuel shut-off valve has manual means to operate	33CFR 183	3.528 ABYC H-24.8.4		<u> </u>	
Fuel lines made of metal or "USCG Type A1" hose		33CFR 183.528		<u> </u>	!
If gasoline tanks: Fuel tank grounded properly	33CFR 183	3.572 ABYC H-24.15	<u> </u>		
Examination notes: Fuel line should be marine approved, not plastic copper, nickel or copper nickel. Fuel lines should be marine approved. See 33CFR 183.520 and 33 CFR 175.201 for venting fuel tanks. EVent screens required.	oved, not plastic hoses. (Check for holes, leaks. Check	direction o	of exhaust disc	scharge.
18 ALTERNATE PROPULSION					
** Vessels under 16 ft. require alternate propulsion((oar or paddle)				
19 ELECTRICAL SYSTEMS				_	
** Approved Marine Alternators				Τ	!
Pos Battery terminals protected or covered 33CFR	R 183.420 & .445 AI	BYC E-10.7.7			
Inspection notes: Check shore power connection for evidence of loc insulation, frayed insulation, loose wires, etc. Battery should be trained at the control of the control			n for traye	ed wires, miss	ing
** Ensure pump(s) work					
Ensure manual bailer aboard & Bilge Slop Retention (auto-off)					
Examination notes: Must be able to shut off automatic float switchor	n the bilge pump				
21 GALLEY / HEATING SYSTEMS					
Approved cooking, heating and lighting systems	46CFR 25.45 &	& ABYC A-3, A-7			
22 STATE REQUIREMENTS					
** Meets any additional State Requirements (docume	ent any deficienies)		$\overline{}$	Т	Т
	, ,				
23 MARINE SANITATION DEVICE					
Certified marine sanitation device: Circle the TYPE:	: 1 11 111	33CFR 159.7		T	
Examination notes: Locking the head door is only applicable to Type Could have overboard discharge mascerator with keyed switch & ke		sure overboard shut off valve is	closed & l	locked	
24 MARPOL TRASH PLACARD & Plan					
Required on vessels >26 ft Pollution placard posted	L	33CFR 151.59(d)			
Examination notes: If vessel is > 39.4 ft. needs a written Trash Disp	posal Plan				
25 OIL POLLUTION PLACARD					
Required on vessels >26 ft Prohibited discharge Wa	arning	33CFR 155.450			
Examination notes: Is vessel operator practicing proper retention of I	bilge slops?				
26 NAVIGATION RULES					
Vessels \geq 12 meters (39.4 ft.) must have a copy of the COI		33CFR 88.05			
Vessels > 20 meters (65 ft.) must have Bridge to Bridge Co	აmms (ch 13)	33CFR 26.03		T	Γ

Vessel Name: DATE:						
27 COMMUNICATINS			UN-SAT	N/A		
Vessels > 65 ft. must have VHF-FM Radio with Ch 22A	33CFR 26.03(a)(1)					
Vessels > 65 ft. FCC ship/Station license: & all TX gear: (EPIRB-Radar etc)	47CFR 80.13 & .25					
Vessels > 65 ft. Valid Radio Operator Permit	47CFR 80.163					
28 EPIRB Hex # :	Expir date:					
** An EPIRB is not required for UPV's (if aboard, it must be registered)	46CFR 25.26-10	T				
7.11. 2.1 11.12 to Hot required for 0.1.1.3 (ly disourd) to must be registered.	100111 25.20 10					
29 DRUG TESTING PROGRAM Name of DER:	Pho	ne:				
Is vessel or Company enrolled in a Randon Drug Program & filed a USCG MIS Report	46CFR 16.230(b) & .5					
Pre-Employment Drug tests or waiver conducted on all crewmembers in						
safety sensitive positions	46CFR 16.10					
Background Check done for all crew hired after 8/1/01	49CFR 40.25					
Drug test records kept on file for 1, 3 or 5 years of durations	46CFR 16.260					
EAP Education & Training done for all crew & Company Policy in place.	46CFR 16.401					
The Crew is aware of available Help Lines						
Method to meet the 2 hr Alcohol testing for a SMI (kits aboard)	46CFR 4.06					
Aware of regulations against operating a vessel while intoxicated	33CFR 95					
Examination notes: Record the Name of MRO:	& Phone ;					
30 EMERGENCY PROCEDURES						
Emergency Check-off list posted in conspicuous location(s)	46CFR 26.03(a) & (b)					
Passenger Counts taken and kept aboard or ashore	46USC 3502					
Aware of Accident and Casualty & SMI reporting regs. 33CFI	R 173.59 & 46CFR 4.05					
Examination notes: Emergency Check-off list could be in a notebook provided it is shown to passengers during Safety Lecture						
31 EMERGENCY INSTRUCTIONS		T				
Safety Orientation given (public announcemnts/ instruction placard(s)) 46CFR 26.031(a)						
Examination notes: Prior to getting underway, the operator shall ensure that suitable public a manner which affords all passengers the opportunity to become acquainted with: Stowage L adjusting life preservers/ The type & location of all lifesaving devices carried aboard/ The loc	ocations of life preservers/ Pro	oper metho	d of donning	_		
32 CHARTS AND NAUTICAL PUBLICATIONS	Γ	1	•			
Paper- Up-to-date Charts of the operating area aboard	46CFR 26.03-4					
Current copy of Coast Pilot & Light List aboard (can be electronic)	46CFR 26.03-4					
Latest copy of Local Notice to Mariners aboard (can be electronic)	46CFR 26.03-4 46CFR 26.03-4					
Current copy of Tide & Current Tables (can be electronic) 46CFR 26 Examination notes: All but the chart can be in electronic form						
Examination notes. An but the chart can be in electronic form						
33 OVERALL VESSEL CONDITIONS						
General condition of the Vessel - Check for any visible hull damage						
NO Oil or debris in the Bilge, Hand Rails secure						
Examination notes: Check hand rails, have Operator operate sea cocks and check engine mounting bolts & look for broken rubber engine mounts & check						
Engine hoses and check for leaks.						
Decal Awarded: YES NO Is this a FOLLOW-UP Exam? NO						
Additional Comments: YES - Date of Previous			.10			
Additional Comments.	TES DUILE OF FIEVIOUS					